

4

SPECIFICATIONS

Items		Model	MSM18NW	
			SINGLE	DOUBLE
Cooling capacity	※1 BTU/h		8,400	8,400X2
Power consumption	※1 W		850	1,700
EER (Double unit operation)			9.9	
SEER (Double unit operation)			10.0	
INDOOR UNIT MODEL			MS09NWX2	
Extenal finish			White	
Power Supply	V, Hz, Phase		115,60,1	
Max. fuse size (time delay)	A		15	
Min. ampacity			0.5	
Fan motor	F.L.A		0.37	
Airflow	Dry	CFM	208-265-328	
Lo-Me-Hi	Wet	CFM	177-226-279	
Moisture removal (Pints/h)			-	
Cond. drain connection OD		in.	5/8	
Dimensions	W	in.	32-1/16	
	D	in.	7-3/16	
	H	in.	10-13/16	
Weight	lbs.		18	
OUTDOOR UNIT MODEL			MUM18NW	
External fnish			Munsell 5Y6.5/1	
Power supply	V, Hz, Phase		208/230,60,1	
Max. fuse sizu (time delay)	A		15X2	
Min. ampacity			14	14+13
Fan motor	F.L.A		1.0	
Compressor	Model		KH122WESX2	
	Winding resistance (at 68°F) Ω		C-R 0.98 C-S 2.21	
	R.L.A		10X2	
	L.R.A		37X2	
Refrigerant control			Capillary tube	
Dimensions	W	in.	33-1/2	
	D	in.	11-7/16 (12-5/8)	
	H	in.	23-7/8	
Weight	lbs.		122	
REMOTE CONTROLLER			Wireless type	
Control voltage (be built-in transformer)			12V DC	
REFRIGERANT PIPING			Not supplied (optional parts)	
Pipe size	Liquid	in.	1/4	
	Gas	in.	3/8	
Connection method	Indoors		Flared	
	Outdoors		Flared	
Between the indoor & outdoor units	Height difference	ft	Max. 25	
	Piping length	ft	Max. 49	

Notes ※1. Rating conditions (cooling) — Inddor : 80°FDB, 67°FWB, Outdoor : 95°FDB, 75°FWB

Operating Range

		Indoor air intake temperature	Outdoor air intake temperature
Cooling	Maximum	90°FDB,71°FWB	115°FDB
	Maximum	67°FDB,57°FWB	67°FDB